

# Enhance™ High Mileage Motor Oil ILSAC GF-6A • API SP

# **Description:**

Enhance™ High Mileage Motor Oils are premium passenger car motor oils (PCMO) specially formulated to protect high mileage engines and extend engine life, specifically for engines with over 75,000 miles. These oils are available in 5W-20, 5W-30 and 10W-30 viscosity grades and are formulated to promote clean engines with excellent control of sludge and other engine deposits that form due to high engine temperatures and combustion exhaust. API SP provides emission system, turbocharger, LSPI and timing chain protection as well as helping to protect engines when operating on ethanol-containing fuels up to E85.

#### **Benefits:**

- Minimizes Sludge & Deposit Formation
- Maximizes Compression to Increase Power Output
- Formulated for Easy Cold Starts

- Helps Reduce Oil Consumption and Leaks
- Protects Against High Temperature Thermal Breakdown

# **Applications:**

These oils meet or exceed the following categories and requirements:

- API Service SP, SN Plus, SN, SM, SL
- ILSAC Starburst GF-6A
- Passenger Car and Light Truck
  Manufacturers Warranty Requirements
  - o GM 6094M (SAE 5W-20, 5W-30, 10W-30)
  - Ford WSS-M2C945-B1 (SAE 5W-20)
  - WSS-M2C946-B1 (SAE 5W-30)
  - Chrysler MS-6395 (SAE 5W-20, 5W-30, 10W-30)
  - Toyota Specifications (SAE 5W-20, 5W-30, 10W-30)
  - Honda Service Fill Specifications (SAE 5W-20, 5W-30, 10W-30)

# Typical Properties:

Enhance™ High Mileage Motor Oil			
SAE Grade	5W-20	5W-30	10W-30
API Gravity @ 60°F	33.3	33.2	33.0
Specific Gravity @ 60°F	0.8585	0.8591	0.8602
Flash, COC, °F	428	420	430
Pour Point, °F	-38	-38	-30
Viscosity @40 °C, cSt	51.8	62.1	62.8
Viscosity @100 °C, cSt	8.7	10.5	10.2
Viscosity Index	147	159	149
API Service Category	SP	SP	SP
ILSAC	GF-6A	GF-6A	GF-6A

### ALWAYS CONSULT OWNER'S MANUAL FOR SERVICE AND FLUID RECOMMENDATIONS