



Enhance™ Full Synthetic Gear Oil

Description:

Enhance™ Full Synthetic Gear Oils are designed for API Service Classification GL-5 and MT-1. This product is formulated with additives to ensure extreme pressure characteristics. It is recommended for use in limited slip and conventional differentials of cars, pick-up trucks, sport utility vehicles and heavy-duty trucks.

Applications:

These gear oils may be used in applications calling for the following:

- SAE J2360
- Mack GO-J (80W-140)
- Mack GO-J Plus (75W-90)

Benefits:

- Excellent Wear Protection
- Full Limited Slip Performance
- Excellent Rust and Corrosion Protection
- Low Pour Point and Anti-Foaming Performance

Typical Properties:

Enhance™ Full Synthetic Gear Oil			
SAE Grade	75W-90	75W-140	80W-140
Viscosity Index	163	180	194
Viscosity @40°C, cSt	100	175	159
Viscosity @100°C, cSt	15.4	27	25.3
Pour Point	-46°F	-49°F	-40°F
Flash Point (COC)	410°F	392°F	420°F

ALWAYS CONSULT OWNER'S MANUAL FOR SERVICE AND FLUID RECOMMENDATIONS

Enhance™ Lubricants
(888) 272-2020 | www.enhanceoil.com