

Enhance™ Multi-Purpose DexMerc® Automatic Transmission Fluid

Description:

Enhance™ Multi-Purpose DexMerc®
Automatic Transmission Fluid meets the original equipment manufacturer's performance requirements of General Motors, Ford and other domestic and imported passenger cars, vans and light trucks where DEXRON® III, H Revision, Automatic Transmission Fluid, or Ford MERCON® fluids are specified.

Also recommended for Detroit Diesel Allison C-3, C-4 applications, and Caterpillar TO-2 applications.

Applications:

Not suitable for use in vehicles requiring Ford Type F, MERCON® V, MERCON® SP, MERCON® LV. Not for use where DEXRON® VI is required. Not for use in Continuously Variable Transmissions (CVT) or Dual Clutch Transmissions (DCT).

Benefits:

- Low Temperature Fluidity for Good Cold-Start Shifting
- Oxidation and Thermal Stability for Long Life
- Resistance to Foaming
- Protects Against Rust, Corrosion and Wear
- Compatible With All Transmission Seal Material

Typical Properties:

Enhance™ Multi-Purpose DexMerc® Automatic Transmission Fluid	
Appearance	Red, Dyed
Viscosity @ 40°C, cSt	33.37
Viscosity @ 100°C, cSt	6.87
Viscosity Index	161
Pour Point	-50°F
API Gravity	33.0
Specific Gravity @ 60°F	0.8602
Pounds per Gallon	7.163
Flash Point COC	405°F
Allison C-4	Y
Cat TO-2	Υ

ALWAYS CONSULT OWNER'S MANUAL FOR SERVICE AND FLUID RECOMMENDATIONS

Enhance™ Lubricants
(888) 272-2020 | www.enhanceoil.com

Technical Data Sheet Revised 08.05.2019