



Enhance™ Rock Drill Oil

Description:

Enhance™ Rock Drill Oils are blended from premium base oils selected for their ability to minimize carbon deposits and fortified with extreme pressure additives, rust and oxidation inhibitors, smoke inhibiting additives and tackiness additives to cling to moving parts of pneumatic percussion tools.

Rock Drill Oils are recommended for use in lubricating all types of pneumatic equipment such as jackhammers, pavement breakers, stoppers, drifters and down-home drills in road construction, quarries and mining.

Applications:

- Pneumatic percussion tools in quarries and road construction and other rock drilling or breaking applications
- Pneumatic tools in a wide variety of applications where EP properties and tack additives are recommended

Typical Properties:

Enhance™ Rock Drill Oil				
SAE Grade	100	220	680	1000
Operating Range, °F, (°C)	40-80 (4-27)	>75 (>24)	>80 (>27)	>80 (>27)
Specific Gravity @ 15.6°C (D-1298)	0.8786	0.8872	0.9194	0.9176
Viscosity @ 40°C, cSt (D-445)	104.3	217.1	670.4	925.3
Viscosity @ 100°C, cSt (D-445)	11.8	19.6	42.5	-
Flash Point, COC (D-92)	200°C	222°C	252°C	240°C
Pour Point (D-97)	-21°C	-15°C	-10°C	-11°C
4-Ball EP Weld Load, kgf (D-2783)	250	250	250	250
ML Identification No.	573440	582354	592149	582856

ALWAYS CONSULT OWNER'S MANUAL FOR SERVICE AND FLUID RECOMMENDATIONS

Enhance™ Lubricants
(888) 272-2020 | www.enhanceoil.com