

# Enhance™ Synthetic Blend Motor Oil



## Description:

Enhance™ Synthetic Blend Motor Oils are formulated for turbo charged and naturally spirited gasoline, propane, natural gas engines in passenger and light duty truck service. These oils are designed for use in US, European and Japanese passenger cars, vans, SUVs and light duty trucks.

## Applications/Approvals:

These oils meet or exceed the following categories and OEM requirements:

- API Service SN Plus
- ILSAC Starburst GF-5
- Passenger Car and Light Truck Manufacturers Warranty Requirements
- Chrysler MS-6395
- Ford WSS M2C945-A, Ford WSS M2C945-B1
- GM dexos1™ Gen 2 (license D10077GE014)

## Typical Properties:

Enhance™ Synthetic Blend Motor Oil						
SAE Grade	0W-20	5W-20	5W-30	10W-30	10W-40	20W-50
Viscosity @ 40°C, cSt	44.89	48.7	58	64.1	101	159
Viscosity @ 100°C, cSt	8.48	8.5	10.2	10.2	15.0	18.8
Viscosity Index	173	151	159	144	154	133
Flash Point	206°C	200°C (392°F)	200°C (392°F)	202°C (395°F)	221°C (430°F)	221°C (430°F)
Pour Point	-48°C	-38°C	-38°C	-34°C	-34°C	-34°C

**ALWAYS CONSULT OWNER'S MANUAL FOR SERVICE AND FLUID RECOMMENDATIONS**

**Enhance™ Lubricants**  
(888) 272-2020 | [www.enhanceoil.com](http://www.enhanceoil.com)