

# Enhance<sup>™</sup> Synthetic Blend Motor Oil ILSAC GF-6A • API SP

# **Description:**

Enhance<sup>™</sup> Synthetic Blend Motor Oils are premium-quality, high detergent automotive engine oils specifically formulated to meet the stringent lubrication requirements of today's engines. Maximum protection against wear, rust, corrosion, oxidative thickening, acid formation, sludge and varnish deposits are provided due to the unique blend of synthetic and high viscosity index Group II mineral oils combined with a carefully selected additive package.

API SP provides emission system, turbocharger, LSPI and timing chain protection and helps to protect engines when operating on ethanol-containing fuels up to E85

### Benefits:

- Improves Fuel Economy
- Enhances Piston Cleanliness
- Increases Emission Protection
- Increases Sludge Protection

# Applications:

These oils meet or exceed the following categories and requirements:

- API Service SP, SN Plus, SN, SM, SL
- ILSAC Starburst GF-6A
- Passenger Car and Light Truck
  Manufacturers Warranty Requirements
  - GM 6094M (SAE 5W-20, 5W-30, 10W-30)
  - Ford WSS-M2C960-A1 (SAE 5W-20)
  - Ford WSS-M2C961-A1 (SAE 5W-30)
  - FCA Chrysler MS-6395 (SAE 5W-20, 5W-30, 10W-30)
  - Toyota Specifications (SAE 5W-20, 5W-30, 10W-30)
  - Honda Service Fill Specifications (SAE 5W-20, 5W-30, 10W-30)

### ALWAYS CONSULT OWNER'S MANUAL FOR SERVICE AND FLUID RECOMMENDATIONS

Typical	Properties:	

Enhance <sup>™</sup> Synthetic Blend Motor Oil				
SAE Grade	5W-20	5W-30	10W-30	
API Gravity @ 60°F	33.4	33.1	30.1	
Specific Gravity @ 60°F	.8581	.8595	.8702	
Flash, COC, °F	428	420	430	
Pour Point, °F	-38	-38	-30	
Viscosity @ 40°C, cSt	50.3	60.8	68.2	
Viscosity @ 100°C, cSt	8.6	10.2	10.3	
Viscosity Index	149	156	137	
API Service Category	SP	SP	SP	
ILSAC	GF-6A	GF-6A	GF-6A	