



Enhance™ Synthetic Blend Motor Oil

Description:

Enhance™ Synthetic Blend Motor Oils are formulated for turbo charged and naturally spirited gasoline, propane, natural gas engines in passenger and light duty truck service. These oils are designed for use in US, European and Japanese passenger cars, vans, SUVs and light duty trucks.

Applications:

These oils meet or exceed the following categories and requirements:

- API Service SN Plus
- ILSAC Starburst GF-5
- Passenger Car and Light Truck Manufacturers Warranty Requirements

Benefits:

- Lubricates, Cools, and Protects Turbo-Charged High-Revving Engines That Operate at High Temperatures
- Protects the Engine in Controlling Varnish, Deposits, Rust, Corrosion, Wear, and Cleanliness
- Designed to Flow at Low Temperatures to Get to Vital Engine Parts Quickly

Typical Properties:

Enhance™ Synthetic Blend Motor Oil						
SAE Grade	0W-20	5W-20	5W-30	10W-30	10W-40	20W-50
Viscosity @ 40°C, cSt	44.89	48.7	58	64.1	101	159
Viscosity @ 100°C, cSt	8.48	8.5	10.2	10.2	15.0	18.8
Viscosity Index	173	151	159	144	154	133
Flash Point	206°C	200°C (392°F)	200°C (392°F)	202°C (395°F)	221°C (430°F)	221°C (430°F)
Pour Point	-48°C	-38°C	-38°C	-34°C	-34°C	-34°C

ALWAYS CONSULT OWNER'S MANUAL FOR SERVICE AND FLUID RECOMMENDATIONS

Enhance™ Lubricants
(888) 272-2020 | www.enhanceoil.com