



Enhance™ TO-4 Drive Train Fluid

Description:

Enhance™ TO-4 Drive Train Fluids are designed to meet the demanding lubricant requirements of late model Caterpillar equipment and other off-road power shift transmissions, hydrostatic transmissions, clutch plates, torque converters, final drives and hydraulic systems.

Applications:

- Caterpillar TO-2 (obsolete) & TO-4
- Allison C-4 (SAE 10W & 30)
- Komatsu Micro-Clutch Equipment
- Vickers (Eaton) M-2950-S
- ZF TE-ML 03C Transmission (SAE 10 & 30)

Benefits:

- Excellent Wear Protection for Critical Transmission and Final Drive Components
- Resistance to Sludge and Varnish Deposit Formation
- Delivers Optimum Friction Properties for Smooth Clutch Plate Operation
- Reduces Brake Chatter in Wet Brake Applications

Typical Properties:

Enhance™ TO-4 Drive Train Fluid			
SAE Grade	10	30	50
API Gravity @ 60°F	30.4	28.4	27
Viscosity @ 40°C, cSt	28.3	75.6	174.5
Viscosity @ 100°C, cSt	5.2	9.7	1.9
Viscosity Index	102	102	102
Flash Point, °C (°F)	208 (406)	232 (450)	217 (423)
Pour Point, °C (°F)	-36 (-33)	-30 (-22)	-24 (-11)
TBN, mg KOH	7.5	7.5	7.5
Zinc, ppm	1100	1100	1100

ALWAYS CONSULT OWNER'S MANUAL FOR SERVICE AND FLUID RECOMMENDATIONS

Enhance™ Lubricants
(888) 272-2020 | www.enhanceoil.com